



Product technical sheet

MAXX 2902



4 - 14 years



30 kids



81,9 m²



Material specification

- Hot-dip galvanized and powder coated steel construction with a diameter of 160 mm,
- Hot-dip galvanized and powder coated steel construction with a diameter of 220 mm,
- Platforms made of durable anti-slip and waterproof HPL plate,
- Side panels made of durable HPL plate, resistant to weather conditions,
- Covers made of stainless steel,
- Stainless steel tube slide,
- Elements made of safe, certified rubber with textile reinforcement,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,



Physical development



balance



sliding



climbing



hiding



community



2 / 3

Surfaces according to EN 1176-1:2017+A1:2023

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

Product technical sheet

MAXX 2902

Amount of safe surface corresponding with free fall height:

HIC <60 50,1 m²

HIC 100 31,8 m²

Data is subject to change without prior notice.

